



PARTS LIST

1	Trisobuild Tailored Profile
2	Nvelope NH2 Aluminium carrier bracket (size TBC in specification)
3	Nvelope Aluminium 'L' rail (Size TBC in specification)
4	Color Headed Stainless steel fixing (TBC in specification)
5	Stainless steel fixing (TBC in specification)
6	Stone fibre slab insulation by others
7	Wallboard by others
8	Loose filled insulation by Others
9	SFS support structure by others
10	Stainless steel fixing (TBC in specification)
11	Optional PVC thermal break, 5mm
12	Cement particle board by others
13	Breather membrane by others

LEGEND

a	Trisobuild Tailored Profiles - Depth Varies
b	Cladding cavity (British standard - 25mm, NHBC - 38mm (baffled joints) and 50mm (open joints))
c	Rigid sheet insulation (project specific depending on specified U-value)
d	Sheeting board - 10mm or 12mm
e	SFS - 90mm...154mm (depending on system specification)
f	Internal plaster board - 30mm

Tata Steel retain the right to amend the construction and technical specifications shown on this drawing without prior notice. Details are typical and it is the responsibility of the installer/designer to ensure the suitability for each specific project, Tata Steel will not be held responsible

TATA STEEL

Sales Office - TEL: 01244 892199
 Technical Office - TEL : 01244 892130

www.tatasteelconstruction.com

PROJECT

Trisobuild Tailor Profiles

TITLE

Typical Horizontal Section

DRAWN BY

JCA

SCALE

NTS

APPROVED BY

TOLERANCES

DATE

18/08/21

DRG. No.

UTP001