


## Span/load tables

R13½/3 Roof profile - 0.9mm aluminium 170N/mm<sup>2</sup>



The span tables below have been created in accordance with EN 1999-1-4 (Eurocode EC9) For the use of roof cladding only.

The values are based on a maximum permitted deflection, span/ 200 under imposed load and span / 150 under wind suction load.

### Safe Imposed (positive) Loads (kN/m<sup>2</sup>)

Span (m)	0.2	0.25	0.3	0.35	0.4	0.45	0.5	0.55	0.6	0.65	0.7	0.75	0.8
Single span	45.43	36.34	30.28	25.95	18.95	13.30	9.69	7.27	5.60	4.40	3.52	2.85	2.35
Double span	33.97	25.56	20.10	16.31	13.55	11.47	9.85	8.56	7.51	6.65	5.94	5.33	4.82
Multi span	39.51	29.85	23.56	19.19	15.99	13.57	11.68	10.17	8.95	7.94	7.10	6.39	5.69

### Safe Wind Suction (negative) Loads (kN/m<sup>2</sup>)

Span (m)	0.2	0.25	0.3	0.35	0.4	0.45	0.5	0.55	0.6	0.65	0.7	0.75	0.8
Single span	107.78	68.99	47.91	35.20	25.32	17.79	12.97	9.75	7.52	5.92	4.74	3.86	3.19
Double span	34.00	25.59	20.13	16.34	13.58	11.50	9.88	8.59	7.54	6.69	5.97	5.37	4.85
Multi span	39.54	29.88	23.60	19.22	16.02	13.60	11.71	10.20	8.98	7.97	7.13	6.42	5.81

**NOTES** Black figures are stress limited, the load shown is the ultimate load divided by 1.5.  
 Blue figures are deflection limited.  
 These tables apply to the metal profile, a check on fastener capacity is also required.  
 Maximum allowable span 800 mm limited by point load, tested to EN 14782 Annex B.  
 Profile selfweight 2.37 kg/m<sup>2</sup> is included, so is not required in the applied loads.

[www.tatasteel.com](http://www.tatasteel.com)

**Tata Steel**  
 Shotton, Deeside, Flintshire, CH5 2NH  
 T: +44 (0) 1244 892 199  
 F: +44 (0) 1244 892 121  
[sales.theworks@tatasteel.com](mailto:sales.theworks@tatasteel.com)  
[www.tatasteelconstruction.com](http://www.tatasteelconstruction.com)

While care has been taken to ensure that the information contained in this publication is accurate, neither Tata Steel Europe Limited, nor its subsidiaries, accept responsibility or liability for errors or for information which is found to be misleading.

Copyright Jun-14  
 Tata Steel Europe Limited