


Tata Steel retain the right to ammend the construction and technical specifications shown on this drawing without prior notice.



All support steelwork by others

TRISOBUILD™ U-VALUES

The depth below refers to both the minimum bracket & insulation height to achieve the stated 'U' value when using a LP1000 liner

|                         |                         |
|-------------------------|-------------------------|
| Depth 140 = 0.30 W/m²K. | Depth 240 = 0.18 W/m²K. |
| Depth 160 = 0.26 W/m²K. | Depth 260 = 0.16 W/m²K. |
| Depth 180 = 0.23 W/m²K. | Depth 280 = 0.15 W/m²K. |
| Depth 200 = 0.21 W/m²K. | Depth 300 = 0.14 W/m²K. |
| Depth 220 = 0.19 W/m²K. |                         |

Junction 'psi' and 'f' values

Ψ = 0.030 W/mK.  
f = 0.96

Stated calculation results are dependent on components being as shown.  
Computer modeled in accordance with EN ISO 10211



**Building Systems UK**  
A Tata Steel enterprise

Technical Office - TEL : 01244 892199  
www.buildingsystemsuk.co.uk

PROJECT

Typical Trisobuild  
VW Details

TITLE

Window Jamb

DRAWN BY

LK

SCALE

NTS

APPROVED BY

PS

TOLERANCES

DATE

01/06/23

DRG. No.

W1-012-02